



Pastille 2

Sconces

YOUR PRODUCT CODE

PAS-2-DD-PC30-27-10_TRIAC_120V-IP20

DESCRIPTION

A fresh chapter in RBW's celebrated Pastille lineup, Pastille 2 reimagines modular lighting with effortless elegance. Inspired by organic forms and architectural precision, its dual-globe design offers a sculptural, versatile solution that balances bold aesthetics with pragmatic functionality.

MATERIALS

Opal Glass, Aluminum Plate

PRODUCT DIMENSIONS

12.5 L x 5.5 W x 4 in D

PRODUCT WEIGHT

3 lbs / 1.4 kg

PERFORMANCE

Estimated Lumens 1210 DC, 940 AC
90 CRI
Power Consumption 15.96W

CERTIFICATION

ADA Compliant
UL Listed
UL Listed to Canadian safety standards.
Suitable for Damp Locations
IP20
IP65

LED LIFESPAN

50k hours

SPECIFICATION LOGIC

DIFFUSER STYLE (GLOBE)

Droplet	DD
Faceted	FF
Ribbed	RR

PRIMARY FINISH COLOR

Matte White	PC20
Silk Grey	PC25
Matte Black	PC30
Breccia	PC31
Vermilion	PC42
Custom Powder Coated	PCXX

CCT

2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

DIMMING / CONTROL / INPUT

0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV
1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
10% Dimming, TRIAC / Forward Phase Control, 120V Input	10_TRIAC_120V
Low Voltage (Driver required, driver not included)	LV

IP RATING

IP 20	IP20
IP 65	IP65

DRAWINGS

Pastille dimensional drawings

