



PERFORMANCE

579 lumens AC
629 lumens DC

CERTIFICATION

UL Listed
UL Listed to Canadian safety standards.
Suitable for Damp Locations
IP65

PATENT FILE NUMBER

US: Filed Application

SUSPENSION

Stem Mount
Stem lengths from 5" to 70", custom lengths available up to 140"
Field trimmable

LED LIFESPAN

50k hours

SPECIFICATION LOGIC

APPLICATION

Pendant

P

SIZE

Small

S

GLASS FINISH

Smoked

S2

STEM FINISH

Vermillion

PC42

STEM LENGTH

5" Stem

5S

14" Stem

14S

28" Stem

28S

42" Stem

42S

56" Stem

56S

70" Stem

70S

COLOR TEMPERATURE

2200K

22

2700K

27

3000K

30

3500K

35

DIMMING / CONTROL / INPUT

0.1% Dimming, 0-10V Control, 120V or 277V Universal Input (Driver External)

0.1_10V_UNV

1% Dimming, 0-10V Control, 120V or 277V Universal Input (Driver External)

1_10V_UNV

1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)

1_TRIAC_120V

Low Voltage (Driver required, driver not included)

LV

10% Dimming, TRIAC / Forward Phase Control, 120V Input (AC)

10_TRIAC_120V

CANOPY

Flat

CN00

Trimless

CN02

IP RATING

IP65

IP65

DRAWINGS

Triple Glazed

Pendants

YOUR PRODUCT CODE

TG- - - - -
- - -

DESCRIPTION

Triple Glazed is a compact pendant defined by a delicious and shapely form of blown glass. Even, upward-bending light develops in a playful, sculptural form.

PRODUCT DIMENSIONS

7"d x 4"h

Stem lengths, 5" - 70"

Additional stem lengths available, contact sales@rbw.com

PRODUCT WEIGHT

2.17lb

