

Crisp Sconce

Sconces



50 Greene St
New York NY 10013
T +1 212 388 1621
sales@rbw.com



For 2D & 3D drawings of all products, including CAD, Revit and IES files, please visit rbw.com

DESCRIPTION

As a versatile flush mount, Crisp's simple, iconic design is suitable for both wall and ceiling installation, indoors and outdoors. The solid glass shade, offered in a range of finishes, is distinguished by its scored surface, adding a subtle textural detail to the environment.

MATERIALS

Cast solid glass, aluminum

COLLECTION NOTES

Luminaire lumens listed are for AC input Triac control. DC input are within photometry downloads.

PERFORMANCE

551 lm (Frosted) | 445 lm (White) | 106 lm (Chrome) | 52 lm (Copper)
Power Consumption 8.5W
Luminaire Watts 7.6W (AC input)
71.7 lm/W (Frosted) | 58 lm/W (White) | 14 lm/W (Chrome) | 7 lm/W (Copper)
90 CRI

LED LIFESPAN

50k hours

CERTIFICATION

ADA Compliant
UL Listed
Suitable for Wet Locations
Suitable for Damp Locations
IP20
IP65



PRODUCT DIMENSIONS

5" Dia. x 3.3" Depth

PRODUCT WEIGHT

3.5 lbs / 2 kg

DIMENSIONAL WEIGHT

3 lbs

YOUR PRODUCT CODE

CR-WS-S13-AA01-27-10_TRIAC_120V-IP20

Specification Logic

GLASS FINISH

White Interior	S10
Chrome Exterior	S11
Frosted	S12
Copper Exterior	S13

BACKPLATE FINISH

Natural Anodized	AA01
Black Anodized	AA04

COLOR TEMPERATURE



2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

DIMMING / CONTROL / INPUT

1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
Low Voltage (Driver required, driver not included)	LV
10% Dimming, TRIAC / Forward Phase Control, 120V Input	10_TRIAC_120V
1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV

IP RATING

IP 20	IP20
IP 65	IP65



CR-WS Crisp Sconce Dimension