



# Dimple Sconce

Sconces

## YOUR PRODUCT CODE

DP-WS-S1-AA01-27-10\_TRIAC\_120V-IP20

## DESCRIPTION

Dimple is a compact and flush-mounted sconce that casts a diffuse and soft, atmospheric light. It is cheekily named for the thick, domed circular diffuser embedded into its front face.

## MATERIALS

Cast solid glass, aluminum

## COLLECTION NOTES

Luminaire lumens listed are for AC input TRIAC control. DC input performance please see photometry downloads. Each form of cast glass is unique. We review each to ensure they conform to ASTM standards, which includes the presence of small air bubbles within the glass.

## PRODUCT DIMENSIONS

5 in dia x 3.3 in D

## PRODUCT WEIGHT

3 lbs / 1.6 kg

## PERFORMANCE

Delivered Lumens 278 lm (Frosted) | 237 lm (White) | 122 lm (Smoked) | 217 lm (Amber)  
Power Consumption 8.5W  
Luminous Efficacy 38.3 lm/W (Frosted) | 32.7 lm/W (White) | 16.9 lm/W (Smoked) | 29.1 lm/W (Amber)  
95 CRI (Smoked) 90 CRI (Frosted/White) 80 CRI (Amber)  
Full detail in [photometry summary](#)

## CERTIFICATION

ADA Compliant  
UL Listed  
• Suitable for Wet Locations  
• Suitable for Damp Locations  
IP20  
IP65  
Declare (LBC Red List Approved)



Declare.

## LED LIFESPAN

50k hours



## SPECIFICATION LOGIC

### GLASS FINISH

|                |    |
|----------------|----|
| White Interior | S1 |
| Smoked         | S2 |
| Amber          | S3 |
| Frosted        | S4 |

### BACKPLATE FINISH

|                  |      |
|------------------|------|
| Natural Anodized | AA01 |
| Black Anodized   | AA04 |

### COLOR TEMPERATURE

|                       |    |
|-----------------------|----|
| 2700K (warm white)    | 27 |
| 3000K (soft white)    | 30 |
| 3500K (neutral white) | 35 |

### DIMMING / CONTROL / INPUT

|   |               |
|---|---------------|
| 10% Dimming, TRIAC / Forward Phase Control, 120V Input                        | 10_TRIAC_120V |
| 1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)       | 1_TRIAC_120V  |
| 1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)   | 1_10V_UNV     |
| 0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External) | 0.1_10V_UNV   |
| Low Voltage (Driver required, driver not included)                            | LV            |

### IP RATING

|       |      |
|-------|------|
| IP 20 | IP20 |
| IP 65 | IP65 |

## DRAWINGS

### DP-WS Dimple Sconce Dimension

